

EROSIONEX

Powder & Liquid

INSTRUCTIONS FOR USE

1. FILL WATER TRUCK AND COVER SURFACE WITH WATER ONLY
2. 1/3 FILL WATER TRUCK OR UNTIL WATER IS FLOWING FREELY THROUGH THE BAFFLES
3. ADD EROSIONEX AND AGITATE WHILST FILLING THE WATER TRUCK
4. HOSE INSIDE TANK AREA WITH WATER, DOING INTERNAL WALLS EDGES AS WELL To ENSURE A GOOD MIX
5. THE MORE YOU AGITATE, THE BETTER THE RESULT, ESPECIALLY APPLYING WITH GRAVITY FEED
6. IN CASE OF ROAD APPLICATION, TWO APPLICATIONS MAY BE NECESSARY FOR INITIAL APPLICATION SUBJECT TO THE CONDITION OF SOIL

2.

7. TAKE NOTICE OF DUST ON THE ROAD WHEN IT RISES TO 1 METRE THEN FALLS BACK ADD ANOTHER COAT OF EROSIONEX.

8. AFTER EACH 5 OR 6 COATS ADD ONE OF WATER ONLY.

5. GOOD TO BRACKISH WATER IS OK, SALT WATER OR CHLORINE TREATED WATER IS NOT.